

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 5

Revision Date
Supersedes Date

12/28/2020 8/29/2018

SECTION 1. IDENTIFICATION

Product identifier: JAX Halo-Guard® FG-2

Part number: HLG02; HLG02N

<u>Identified uses:</u> Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

Supplier: JAX INC.

W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency Phone: 262-781-8850 Fax: 262-781-3906

contact:

Emergency telephone: INFOTRAC:

North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: While this material is not classified as hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS

contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and

available for employees and other users of this product.

Label elements

Plctograms: Not applicable

Signal word: Not applicable

Hazard statements: Not applicable

Precautionary Avoid release to the environment. Dispose of contents/ container to an approved waste disposal plant.

statements:

Hazards not otherwise Not applicable

classified:

Additional information: Harmful to aquatic life with long lasting effects.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	<u>Chemical name</u>	<u>%</u>	CAS #	<u>Impurities</u>
	Distillates (petroleum), solvent-refined heavy paraffinic*	10-<20	64741-88-4	None
	Calcium carbonate (dust)	10-<20	471-34-1	None
	Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts	1-<5	68584-23-6	None
	Zinc oxide	1-<5	1314-13-2	None
	Calcium dodecylbenzene sulphonate	1-<5	26264-06-2	None
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	1-<5	68411-46-1	None
	Sulfonic acids, petroleum, calcium salts	1-<5	61789-86-4	None
	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	1-<5	70024-69-0	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physician.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

Page 2 of 5
Revision Date

Revision Date 12/28/2020 Supersedes Date 8/29/2018

Ingestion:

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention.

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

Most important

No further relevant information available.

symptoms and effects, both acute and delayed:

Indication of any

See First

immediate medical attention and special treatment available: See First aid measures (above).

General information: No further relevant information available. **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing

Carbon dioxide (CO2), dry chemical or water spray. Fight larger fires with water spray or alcohol resistant foam.

media:

Unsuitable extinguishing media:

Do not use direct stream of water.

Specific hazards:

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool. Burning

produces noxious and toxic fumes.

Advice for firefighters:

Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

spaces or as otherwise needed. Prevent fire-extinguishing water from contaminating surface water or the groundwater

system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

procedures:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Methods for containment and cleaning up Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Keep container closed when not in use.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry place in tightly sealed containers. Store in out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from strong acids, strong bases, and strong oxidizing agents. Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

paraffinic*

Workplace exposure limits:

<u>Chemical name</u>

Distillates (petroleum), solvent-refined heavy

Exposure limit and source

5 mg/m³ (oil mist), OSHA

Calcium carbonate (dust)

) TWA (respirable) = 5 mg/m³ (NIOSH REL)

Not available

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium

salts

Zinc oxide 2 mg/m ³ (TWA), ACGIH

10 mg/m³ (STEL), ACGIH

Calcium dodecylbenzene sulphonate

Benzenamine, N-phenyl-, reaction products with 2,4,4- Not available

trimethylpentene

Sulfonic acids, petroleum, calcium salts No

Not available

Not available

Page 3 of 5 JAX Halo-Guard® FG-2

Revision Date Supersedes Date

12/28/2020 8/29/2018

Benzenesulfonic acid, mono-C16-24-alkyl derivatives,

calcium salts

Not available

Exposure controls

Engineering controls: Good general ventilation should be sufficient to control vapors under ambient conditions. Additional ventilation or exhaust

may be required to maintain air concentrations below recommended exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of work period. Product is readily removed from

skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

Solubility in water:

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

White semi-solid with mild petroleum odor **Upper flammability limit:** Not determined Appearance / odor:

> Lower flammability limit: Not determined

Semi-solid Physical state: Not available Vapor pressure:

Odor threshold: Not available Vapor density:

Not available

Negligible

Not available pH: Melting / freezing point: Not available Relative density: 0.95-1.05

Initial boiling point Not available

and boiling range:

Flash point: 350°F (177°C), ASTM D 92 Partition coefficient (n-Not available

octanol/water):

Not available **Autoignition temperature:** Not available

Decomposition temperature: Not available

Flammability (solid, gas): Not applicable Viscosity: Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Stable under recommended conditions. **Chemical stability:**

Possibility of

Evaporation rate:

Hazardous reactions are not expected to occur.

hazardous reactions:

Conditions and Keep away from heat, sparks, open flames and other sources of ignition. Keep out of direct sunlight. Avoid strong acids, strong materials to avoid:

bases, and strong oxidizing agents.

Hazardous Carbon oxides, metal oxides, nitrogen oxides (NOx), and sulfur oxides.

decomposition products:

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact: No known significant effects or critical hazards. Skin contact: No known significant effects or critical hazards. Inhalation: No known significant effects or critical hazards. Ingestion: No known significant effects or critical hazards.

LC₅₀ Components Component LD₅₀

information: Not available Not available Distillates (petroleum), solvent-refined heavy

paraffinic*

Calcium carbonate (dust) Not available Not available

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium Not available Not available

salts

Zinc oxide 5000 mg/kg (oral, rat) Not available Calcium dodecylbenzene sulphonate >4199 mg/kg (dermal, rabbit) Not available

Page 4 of 5 JAX Halo-Guard® FG-2

Revision Date Supersedes Date

Not available

Not available

Not available

12/28/2020 8/29/2018

Benzenamine, N-phenyl-, reaction products with 2,4,4- >2000 mg/kg (oral, rat)

Benzenesulfonic acid, mono-C16-24-alkyl derivatives,

trimethylpentene

Sulfonic acids, petroleum, calcium salts >5000 mg/kg (oral, rat)

Not available

Not available

calcium salts

Information on physical, chemical and toxicological effects

Symptoms: See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure No further relevant information available.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

Not determined

toxicity:

Effects:

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Aquatic Acute Hazard (Cat. 3); Aquatic Chronic Hazard (Cat.3)

L(E)C₅₀ Components Component information:

Distillates (petroleum), solvent-refined heavy

paraffinic*

Calcium carbonate (dust) Not available Benzenesulfonic acid, C10-16-alkyl derivatives, calcium Not available

Zinc oxide 1.1 mg/l/96h [Oncorhynchus mykiss (rainbow trout)]

Calcium dodecylbenzene sulphonate 2.5 mg/l/48h [Daphnia magna (Water flea)] Benzenamine, N-phenyl-, reaction products with 2,4,4- >71 mg/l/96h [Danio rerio (zebra fish)]

trimethylpentene

Sulfonic acids, petroleum, calcium salts >100 mg/l/48h [Daphnia magna (Water flea)]

Benzenesulfonic acid, mono-C16-24-alkyl derivatives, Not available

calcium salts

Persistence and degradability:

Not determined

Bioaccumulative

potential:

methods:

Not determined

Not available Mobility in soil: Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment

Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions. Dacking

	Proper Shipping Name:	UN Number:	Class:	Group:	Remarks:
<u>U.S. D.O.T</u> .	Not regulated	None	None	None	None
ADR/RID	Not regulated	None	None	None	None
<u>IMDG</u>	Not regulated	None	None	None	None
<u>IATA</u>	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA Section 302 This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

Extremely Hazardous Substances:

None

Page 5 of 5 JAX Halo-Guard® FG-2 **Revision Date**

12/28/2020 8/29/2018 **Supersedes Date**

SARA Section 304

Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to

reporting to the National Response Center under CERCLA: **CERCLA Hazardous**

Substances:

None

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis threshold value:

Chemicals:

Zinc oxide, CAS # 1314-13-2, present at <2.5%

TSCA Inventory: All components are either listed or exempted from listing on the TSCA Inventory.

U.S. State Regulations

California Proposition

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California

Proposition 65 at levels which would be subject to the proposition.

65 Status: California

Proposition 65 Listed Components: None

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

information required by those regulations.

Japan MITI: Not available Australia: Not available Switzerland: Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Sections 2 & 12 12/28/2020 **Revision Date:**

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.

*** END OF SDS ***