

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 5

Revision Date Supersedes Date

8/28/2018 9/12/2017

SECTION 1. IDENTIFICATION

Product identifier: JAX Halo-Guard® FG-PM

Part number: HLGPM; HLGPMN

Identified uses: Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

JAX INC Supplier:

W134 N5373 Campbell Drive

Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency Phone: 262-781-8850 Fax: 262-781-3906

contact:

Emergency telephone: INFOTRAC:

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS

contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and

available for employees and other users of this product.

Label elements

Pictograms: Not applicable

Not applicable Signal word: **Hazard statements:** Not applicable **Precautionary** Not applicable

statements:

Hazards not otherwise Not applicable.

classified:

Additional information: Not applicable

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	<u>Chemical name</u>	<u>%</u>	CAS #	<u>Impurities</u>
	White mineral oil (petroleum)	50-<70	8042-47-5	None
	Distillates (petroleum), solvent-refined heavy paraffinic*	10-<20	64741-88-4	None
	Calcium carbonate (dust)	10-<20	471-34-1	None
	Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts	1-<5	68584-23-6	None
	Zinc oxide	1-<2.5	1314-13-2	None
	Calcium dodecylbenzene sulphonate	1-<3	26264-06-2	None
	Sulfonic acids, petroleum, calcium salts	1-<5	61789-86-4	None
	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	1-<2.5	68411-46-1	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

8/28/2018 **Revision Date** Supersedes Date 9/12/2017

Page 2 of 5

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

Most important No further relevant information available.

symptoms and effects, both acute and delayed:

Indication of any

See First aid measures (above).

immediate medical attention and special treatment available:

General information: No further relevant information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be

used to keep fire-exposed containers cool.

extinguishing media:

Do not use direct stream of water.

Specific hazards:

Unsuitable

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

Advice for firefighters:

Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

procedures:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Methods for containment and cleaning up

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits:

Chemical name Exposure limit and source 5 mg/m³ (oil mist), TWA, ACGIH White mineral oil (petroleum) Distillates (petroleum), solvent-refined heavy 5 mg/m3 (oil mist), OSHA

paraffinic*

Zinc oxide

TWA (respirable) = 5 mg/m3 (NIOSH REL) Calcium carbonate (dust)

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium

salts

2 mg/m³ (TWA), ACGIH 10 mg/m3 (STEL), ACGIH

Not available

Calcium dodecylbenzene sulphonate Not available Sulfonic acids, petroleum, calcium salts Not available Benzenamine, N-phenyl-, reaction products with 2,4,4-Not available

trimethylpentene

Page 3 of 5 JAX Halo-Guard® FG-PM

8/28/2018 **Revision Date** 9/12/2017 Supersedes Date

Exposure controls

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

Vapor density:

Carbon monoxide, carbon dioxide, oxides of nitrogen (NOx), sulphur oxides, smoke and irritating vapors as products of

Not available

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Cream-colored semi-solid with mild petroleum Appearance / odor:

odor

Semi-solid **Physical state:**

Odor threshold: Not available

Not available

Melting / freezing point: Not available

Initial boiling point

and boiling range:

Flash point: 356°F (180°C), ASTM D 92

Evaporation rate: Not available

Flammability (solid, gas): Not applicable **Upper flammability limit:** Not available

Lower flammability limit: Not available

Not available Vapor pressure:

Not available

Not available

Not available

0.95-1.05 Relative density:

Solubility in water: Negligible

Partition coefficient

(n-octanol/water):

Autoignition temperature: Not available

Decomposition temperature: Not available

Viscosity: Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Not available

Stable under recommended conditions. **Chemical stability:**

Possibility of **Conditions and**

hazardous reactions:

Hazardous reactions are not expected to occur.

Conditions to avoid: Direct heating, dirt, chemical contamination, sunlight, UV or ionizing radiation. Exposure to moisture. materials to avoid: Incompatible materials: Strong acids, strong bases, and oxidizing materials.

Hazardous decomposition

incomplete combustion.

products:

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eve contact: No known significant effects or critical hazards. Skin contact: No known significant effects or critical hazards. Inhalation: No known significant effects or critical hazards. No known significant effects or critical hazards. Ingestion:

LC₅₀ **Components** <u>LD</u>50 Component

>5000 mg/kg (oral, rat) information: White mineral oil (petroleum) Not available

Distillates (petroleum), solvent-refined heavy

paraffinic*

Calcium carbonate (dust) Not available Not available Not available Not available

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium

salts

Zinc oxide 5000 mg/kg (oral, rat) Not available Calcium dodecylbenzene sulphonate >4199 mg/kg (dermal, rabbit) Not available

Page 4 of 5 JAX Halo-Guard® FG-PM

Benzenamine, N-phenyl-, reaction products with 2,4,4- >2000 mg/kg (oral, rat)

Revision Date Supersedes Date 8/28/2018 9/12/2017

Sulfonic acids, petroleum, calcium salts

>5000 mg/kg (oral, rat)

Not available Not available

trimethylpentene

Information on physical, chemical and toxicological effects

Symptoms: See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects: No further relevant information available.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

Numerical measures of Not determined

toxicity:

Ecotoxicity:

SECTION 12. ECOLOGICAL INFORMATION

L(E)C₅₀ Component Components

information: White mineral oil (petroleum) Not available

Distillates (petroleum), solvent-refined heavy

paraffinic*

Not available

Calcium carbonate (dust) Not available Benzenesulfonic acid, C10-16-alkyl derivatives, calcium Not available

salts

Zinc oxide 1.1 mg/l/96h [Oncorhynchus mykiss (rainbow trout)]

Not available

Calcium dodecylbenzene sulphonate 2.5 mg/l/48h [Daphnia magna (Water flea)] Sulfonic acids, petroleum, calcium salts >100 mg/l/48h [Daphnia magna (Water flea)] Benzenamine, N-phenyl-, reaction products with 2,4,4->71 mg/l/96h [Danio rerio (zebra fish)]

trimethylpentene

Not determined

Not determined

Persistence and

degradability:

Bioaccumulative potential:

Mobility in soil: Not available Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

methods: Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	UN Number:	Hazard <u>Class:</u>	Packing Group:	Remarks:
<u>U.S. D.O.T.</u>	Not regulated	None	None	None	None
ADR/RID	Not regulated	None	None	None	None
<u>IMDG</u>	Not regulated	None	None	None	None
<u>IATA</u>	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: SARA Section 302 **Extremely Hazardous** None

SARA Section 304

Substances:

CERCLA Hazardous

Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA:

Page 5 of 5 JAX Halo-Guard® FG-PM

8/28/2018 **Revision Date** 9/12/2017 **Supersedes Date**

Calcium dodecylbenzenesulphonate, CAS # 26264-06-2, RQ = 1000 lbs. Substances:

Note: Calculated product RQ (lbs.) exceeds reasonably attainable upper limit.

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis threshold value:

Chemicals:

Zinc oxide, CAS # 1314-13-2, present at <2.5%

TSCA Inventory: All components are either listed or exempted from listing on the TSCA Inventory.

U.S. State Regulations

California Proposition

65 Status:

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California

Proposition 65 at levels which would be subject to the proposition.

California

Proposition 65 Listed Components:

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

information required by those regulations.

Japan MITI: Not available Australia: Not available Switzerland: Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Sections 2, 3, 4, 9, 11 and 12.

None

8/28/2018 **Revision Date:**

The information and recommendations contained herein are, to the best of JAX INC's knowledge and belief, accurate and reliable as of the date issued. JAX INC makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC's interpretation of the available data.

*** END OF SDS ***