

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 4

Revision Date 9/29/2016 **Supersedes Date** 11/11/2015

SECTION 1. IDENTIFICATION

Product identifier: JAX Electrical Contact Cleaner Non-Flammable Formula (Aerosol)

JAX124 Part number:

Identified uses: Solvent cleaner for electronic instruments and devices

Uses advised against: Any uses not listed above. Supplier:

Pressure-Lube Inc. JAX

W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency

contact:

Phone: 262-781-7660

INFOTRAC: **Emergency telephone:**

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

Fax: 262-781-3906

SECTION 2. HAZARD(S) IDENTIFICATION

Classification: Gases under Pressure (Compressed Gas); Eye Irritation Cat. 2

Label elements

Pictograms:



Signal word: Warning

Hazard statements: Contains gas under pressure; may explode if heated. Causes serious eye irritation.

Precautionary Wash skin thoroughly after handling. Wear eye protection/ face protection. IF IN EYES: Rinse cautiously with water for several statements:

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/

attention. Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise Not applicable.

classified:

Additional information: 30.0 % by mass of the contents are flammable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Chemical name	<u>%</u>	CAS #	<u>Impurities</u>
	1,1,1,2-Tetrafluoroethane	50-100	811-97-2	None
	Propan-2-ol	10-25	67-63-0	None
	Acetone	10-25	67-64-1	None

SECTION 4. FIRST-AID MEASURES

First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

Most important Causes serious eye irritation.

symptoms and effects, both acute and delayed:

Indication of any No further relevant information available.

immediate medical attention and special treatment available:

General information: No further relevant information available.

Page 2 of 4

Revision Date
Supersedes Date

9/29/2016 11/11/2015

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing

media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be

used to keep fire-exposed containers cool.

Do not use direct stream of water.

<u>Unsuitable</u>

extinguishing media:

Specific hazards:

Contains gas under pressure; may explode if heated. Use water spray to keep containers cool.

Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

and the influence of the control of

Environmental precautions:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or

Methods for containment and cleaning up **Land spill:** Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by

skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Keep away from heat and direct sunlight. Keep away from ignition sources - Do not smoke. Protect against electrostatic discharges. Ensure good ventilation/exhaustion at the workplace.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Observe official regulations on storing packagings with pressurized containers. Store away from oxidizing agents. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure

Chemical name

Exposure limit and source

limits: 1,1,1,2-Te

1,1,1,2-TetrafluoroethaneLong-term value: 4240 mg/m³, 1000 ppmPropan-2-olShort-term value: 1250 mg/m³, 500 ppmLong-term value: 999 mg/m³, 400 ppmAcetoneShort-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

Exposure controls

Odor threshold:

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / odor: Colorless liquid with alcohol odor

Not available

<u>Upper flammability limit</u>: Not available

Lower flammability limit: Not available

Physical state: Liquid and compressed gas in aerosol can Vapor pressure:

Vapor density:

pH: Not available

Not available

Not available

Page 3 of 4

Revision Date Supersedes Date 1

9/29/2016 11/11/2015

Melting / freezing point: Not available

Initial boiling point

Not available

and boiling range:

Evaporation rate:

Flammability (solid, gas):

Flash point:

Not available

Not available

Not applicable

Solubility in water:

Not available

Not available

Partition coefficient

Relative density:

Not available

(n-octanol/water):

Autoignition temperature:

Not available

Decomposition temperature: Not available

Viscosity: Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Chemical stability: Stable under recommended conditions.

Possibility of hazardous reactions:

Hazardous reactions are not expected to occur.

Conditions and materials to avoid:

Avoid caustics, amines, alkanolamines, aldehydres, ammonia, strong oxidizing agents, chlorinated compounds, strong alkalis.

Hazardous decomposition

products:

Hazardous decomposition products include carbon monoxide, carbon dioxide, and hydrogen fluoride.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact: Causes serious eye irritation.

Skin contact:No known significant effects or critical hazards.Inhalation:No known significant effects or critical hazards.Ingestion:No known significant effects or critical hazards.

Component Components LD₅₀ LC₅₀

information: 1,1,1,2-Tetrafluoroethane Not available Not available

Propan-2-ol 5045 mg/kg (oral, rat) 30 mg/l/4h (inhalation, rat)

Acetone 5800 mg/kg (oral, rat) Not available

Information on physical, chemical and toxicological effects

See Section 4 of this SDS for symptoms.

Delayed and immediate effects, and chronic effects, from short and long-terms exposure

Effects: No further relevant information available.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated

carcinogen by NTP.

Numerical measures of

toxicity:

Not determined

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Not available

Component Components

information: 1.1.1.2 Totrafluoroothana Not ava

1,1,1,2-TetrafluoroethaneNot availablePropan-2-olNot availableAcetoneNot available

Persistence and

degradability:

Not determined

<u>Bioaccumulative</u>

Not determined

potential:

Mobility in soil: Not available

Page 4 of 4

Revision Date Supersedes Date

9/29/2016 11/11/2015

Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. methods:

Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	<u>UN Number</u> :	Hazard <u>Class:</u>	Packing Group:	Remarks:
U.S. D.O.T.	Aerosols, non-flammable	UN1950	2.2	None	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Aerosols	UN1950	2.2	None	None
<u>IMDG</u>	Aerosols	UN1950	2.2	None	None
<u>IATA</u>	Aerosols, non-flammable	UN1950	2.2	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA Section 302

This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

Extremely Hazardous

Substances:

Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA:

CERCLA Hazardous Substances:

SARA Section 304

None

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

Chemicals:

TSCA Inventory: All components of this material are on the U.S. TSCA Inventory.

U.S. State Regulations

California Proposition

This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

65 Status: California

None

Proposition 65 Listed Components:

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the

information required by those regulations.

Japan MITI: Not available Australia: Not available Switzerland: Not available

SECTION 16. OTHER INFORMATION

Sections Revised: Section 2 9/29/2016 **Revision Date:**

The information and recommendations contained herein are, to the best of Pressure-Lube Inc. JAX's knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. JAX makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. JAX shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc. JAX's interpretation of the available data.